



Dawnprene TPV TK-65A

TPV

Features:

A soft, colour thermoplastic vulcanizate (TPV) in the thermoplastic elastomer (TPE) family. This material combines good physical properties, chemical resistance and elasticity, designed for track applications. It is polyolefin based and completely recyclable.

RoHS	RoHS		
	3-8mm		
	/		
	2018-5-25		
	1.42	g/ m ³	ASTM D792
(Shore A,15sec ,2	63.4	A	ASTM D2240
100% - 2	2.36	Mpa	ASTM D412
- 2	4.18	Mpa	ASTM D412
- 2	442	%	ASTM D412
- 2	24.2	KN/m	ASTM D624
	25	mm/min	GB/T8410
<p>1.Dawnprene TPV PVC Dawnprene TPV is incompatible with PVC materials, hence must clean the equipment before using.</p>			
<p>2. 120 100 2 , . Above testing data is tested by molding sample block, cutting by the sheet size is 120 100 2 .</p>			
<p>3. . The properties is typical performance, is not regarding as technical index or agreement.</p>			
<p>SHANDONG DAWN POLYMER CO.,LTD : .265703 Address: Zhen'ing Road, Longgang Economic Zone, Longkou, Shandong, China. 265703 ()0086-535-8868588;()0086-535-8833988 Tel:(Foreign Trade) 0086-535-8868588;(Domestic Trade)0086-535-8833988</p>			