

Dawnprene TPE 6302-PB

TPE

TPE

Features:

It is a natural, thermoplastic elastomer (TPE) material. This material combines good physical properties, chemical resistance and elasticity, designed for injection applications. This grade of TPE can be processed on conventional thermoplastics equipment for injection. It is completely recyclable.

| (GENERAL) | |
|------------------|-------------------|
| (Application) | general injection |
| RoHS Compliance | RoHS |
| (Color) | Natural |
| (Form) | Pellet |



| | | | | | | | |
|---|--------|---------|---------|---------|---------|---------|-------|
| R | | | | | | | |
| 4 | 16 170 | 170-190 | 180-210 | 180-210 | 180-200 | 180-190 | 50-70 |

1. Dawnprene TPE PVC

Dawnprene TPE is incompatible with PVC materials, hence must clean the equipment before using.

2. 120 100 2 , .
Above testing data is tested by injection sample block, cutting by the sheet size is 120 100 2 .

3. .
The properties is typical performance, is not regarding as technical index or agreement.

4. Any reprocessing must follow the above instructions, and ensure no content impurity.

5. Above instructions for reference only, different equipment might have difference parameters, please adjust accordingly with different mold and product shape.

SHANDONG DAWN POLYMER CO.,LTD

: . 265703

Address: Zhenxing Road, Longgang Economic Zone, Longkou, Shandong, China. 265703

() 0086-535-8868588; () 0086-535-8833988

Tel: (Foreign Trade) 0086-535-8868588; (Domestic Trade) 0086-535-8833988